



Two Tank Softener

Features

- Eliminates Hardness (Calcium & Magnesium)
- Mechanical Meter Initiated Controls
- U. S. Made Poly wound mineral tank with high flow 1" distribution tube
- Plastic bypass with 1" MNPT yoke
- Standard 18" X 33" brine tank with high flow brine safety float assembly, overflow fitting, grid plate, and brine well
- 5 year warranty

General Specifications	27014842	27014843
Grains Capacity / Regeneration	32,000	48,000
Maximum Raw Water Hardness (Grains)	75	100
Maximum Clear Iron / Manganese (ppm)	5	5
Salt Used / Regeneration (Lbs)	15	24
Cation Exchange Resin (Cu Ft)	1.00	1.50
Mineral Tank (Polyglass)	9 x 48	10 x 54
Brine Tank (Polyethylene)	18 x 33	18 x 33
Service Flow Rate (GPM)	10	11
Backwash Flow Rate (GPM)	2.0	2.4
Space Required (D x W x H)	18 X 27 X 55	18 X 28 X 61
Approximate Shipping Wt.	100 LBS	133 LBS

ASSEMBLED IN
USA ★

* The pressure drop does not exceed 15.0 psi at the service flow rate.
** Factory Salt Setting; 9lbs./cuft.