

Sidekick

Revolutionary Features



- Removes Iron and Sulfur without chemicals
- Air is injected into the top of the tank converting ferrous iron to ferric iron after untreated water has passed through the control valve preventing the control valve from fouling with iron
- Home Connect Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Air draw cycle can be initiated without a backwash cycle saving 1000's of gallons of water annually
- The control valve slowly releases compressed air charge prior to backwash cycle eliminating the explosive blast that can dislodge the drain line
- Adjustable cycle times
- Plastic bypass with 1" MNPT yoke
- Poly wound mineral tank with high flow 1" distribution tube
- Smart Blend filter media
- Top cap fill opening for ease of service
- Compatible with any type of well pump system
- Patent 9212070, other patents pending
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure

10 YEAR WARRANTY

GENERAL SPECIFICATIONS

Filteration Media Capacity (CU. FT.)	1.5 cu. ft.
Mineral Tank	10 x 54
Service Flow Rate - Continuous (GPM)	5
Service Flow Rate - Intermittent (GPM)	7
Backwash Flow Rate (GPM)	5.0
Gallons Used / Backwash	106
Space Required (D x W x H inches)	10 x 21 x 61
Approximate Shipping Weight	160

Note: Caution should always be used in sizing filters. Always choose a unit by satisfying the Backwash Requirement. Use of a flow control in the Service Line is highly recommended. Consult the factory or your field sales person with questions.

